

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Motorsports
- > Silk screening
- > Plastering
- > Stucco masking
- > HVAC duct systems
- > Bundling, seaming, sealing & splicing

ADVANTAGES AND BENEFITS

- > Waterproof backing
- > High tensile strength
- > Conformable
- > Excellent holding power


CONSTRUCTION

Overall Grade/Function: Premium Grade

Backing: Waterproof, polyethylene film with a polyester/cotton blend cloth carrier

Adhesive: Natural Rubber

COLOR(S)



STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

| | STANDARD | METRIC |
|-----------------------------|-----------------|--------------|
| Tensile Strength | 40 lbs/in width | 70.1 N/10 mm |
| Adhesion to Stainless Steel | 55 oz/in width | 6.02 N/10 mm |
| Thickness | 12.5 mils | 0.32 mm |
| Elongation | 10 % | 10 % |
| Service Temperature Range | 50 F to 200 F | 10 C to 93 C |

APPLICABLE SPECIFICATIONS

Tested in accordance with UL723; Flame Spread Index 10; Smoke Development Index 10.

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

