

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Premium waterproof packaging tape meeting government specifications
- > Masking silk screen frames
- > To moisture proof cartons, canisters and tubing

ADVANTAGES AND BENEFITS

- > Waterproof backing
- > Durable
- > Very high holding power
- > Conformable
- > Lusterless backing
- > High tensile strength

CONSTRUCTION

Overall Grade/Function: Premium Grade Lusterless

Backing: Waterproof, polyethylene film with a polyester/cotton blend cloth carrier

Adhesive: Natural rubber



COLOR(S)

- Black (BLK)
- Dark Green (DGN)
- White (WHI)
- Red (RED)
- Olive Drab (OLV)

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	40 lbs/in width	70.1 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Thickness	12.0 mils	0.30 mm
Elongation	10 %	10 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

Conforms to ASTM-D 5486M-99, Type IV, Specifications – replaced PPP-T-60E, Type IV, Class I (Canceled 1995)

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.